



# 1.1KW 9 Outputs Switching Power Supply

TECHNOLOGIES

Input Voltage and Frequency	85 to 264 VAC, 47 to 66Hz
Input Current	16A Maximum
Inrush Current	At 264 VAC 80 Amps Max. (nominal at 120VAC 35Amps)
Number of Output	9ea
Output Power	1.1KW
PFC	ACTIVE PFC
Efficiency	74%
Power Factor Correction	>0.99
Conducted EMI	EN55011/CISPR11 Group 1 Class A
Operating Temperature	0~ 55°C
Humidity	Up to 95% RH from 0C to 40°C. Up to 65% RH from 55°C to 75°C.
Cooling	Internal fan provides forced-air cooling
Isolation	AC 3KV/ 1minute
Standby Output	+10V DC
Remote On/Off	YES
Protection	OVP, OCP, OTP, SCP, UVP
Safety Agency Certification	cNRTL, CE
Size (W x H x D)	328.12 x 148.97 x 253.7(mm)

## ❖ Output Information

Output	Set Voltage	Tolerance @ Set Load	Set Load	Total Tolerance	Min Load	Max Load
1	5.0V	NA	NA	0.25V/-0.125V	1A	95A
2	12.0V			0.60V/-0.36V	0A	15A
3	-12.0V			-0.60V/0.36V	0A	15A
4	24.0V			1.2V/-0.72V	0A	15A
5	-24.0V			-1.2V/0.72V	0A	15A
6	-5.2V			-0.26V/0.156V	0A	60A
7	-2.0V			-0.1V/0.1V	0A	30A
8	10.0V			±5%	0.01A	0.125A
9	14.0~26.3V			±5%	1A	4A