



175W 6 Outputs Switching Power Supply

TECHNOLOGIES

Input Voltage and Frequency	88 VAC-269 VAC/45Hz-66Hz, 88 VAC-135 VAC/360Hz-440Hz
Input Current	3A Maximum
Inrush Current	Less than 140A
Number of Output	6ea
Output Power	175W
PFC	ACTIVE PFC
Efficiency	70%
Power Factor Correction	>0.99
Conducted EMI	EN55011 Level A
Operating Temperature	0 ~ 60°C
Humidity	15% ~ 95% RH at 40°C. (5day)
Cooling	Internal fan provides forced-air cooling
Isolation	AC 3KV/ 1minute
Standby Output	NO
Remote On/Off	YES
Protection	OVP, OCP, OTP, SCP, UVP
Safety Agency Certification	cNRTL, CE, CB
Size (W x H x D)	359 x 71.6 x 70.5(mm)

❖ Output Information

Output	Set Voltage	Tolerance @ Set Load	Set Load	Total Tolerance	Min Load	Max Load
1	3.3V	NA	NA	3.24 ~ 3.46V	0.15A	4A
2	12V			-0.5 ~ +0.5V	0A	2A
3	17V			17 ~ 18V	0.15A	2A
4	-17V			-17 ~ +17V	0.15A	2A
5	6.7V			6.7 ~ 7.2V	0.15A	4A
6	-6.7V			-6.7 ~ -7.2V	0.8A	6A