



192W 1 Outputs Switching Power Supply

TECHNOLOGIES

| | |
|-----------------------------|--------------------------------|
| Input Voltage and Frequency | AC 90V ~ 260V, 47Hz ~ 63Hz |
| Input Current | 6A Maximum |
| Inrush Current | Less than 60A |
| Number of Output | 1ea |
| Output Power | 192W |
| PFC | PASSIVE PFC |
| Efficiency | 72% |
| Power Factor Correction | >0.6 |
| Conducted EMI | EN 55014-1, EN 55014-2 CLASS B |
| Operating Temperature | 0~40°C |
| Humidity | 30% ~ 85% RH (non-condensing) |
| Cooling | Convection |
| Isolation | AC 3KV/ 1minute |
| Standby Output | NO |
| Remote On/Off | NO |
| Protection | OCP, OVP ,OTP ,SCP |
| Safety Agency Certification | CE, CB, CCC, PSE |
| Size (W x H x D) | 194 x 95 x 64(mm) |

❖ Output Information

| Output | Set Voltage | Tolerance @ Set Load | Set Load | Total Tolerance | Min Load | Max Load |
|--------|-------------|----------------------|----------|-----------------|----------|----------|
| 1 | 24.0V | NA | NA | ±10% | 0A | 8A |

❖ Operating Load Condition

