



# 292W 9 Outputs Switching Power Supply

<b>Input Voltage and Frequency</b>	88 – 135VAC (Range1), 193 – 269VAC or 273 – 381VDC (Range2), 45~66Hz AC (Voltage ranges 1 and 2) 360~440Hz AC, 100~135VAC (Voltage range 1 only)
<b>Input Current</b>	7.2A Maximum
<b>Inrush Current</b>	Less than 140A
<b>Number of Output</b>	9ea
<b>Output Power</b>	292W
<b>PFC</b>	ACTIVE PFC
<b>Efficiency</b>	65%
<b>Power Factor Correction</b>	>0.9
<b>Conducted EMI</b>	EN55011 Level A
<b>Operating Temperature</b>	0~55C
<b>Humidity</b>	15% ~ 95% RH at 40 degrees C
<b>Cooling</b>	Cooling is provided by externally provided forced air.
<b>Isolation</b>	Complies with CSA61010
<b>Standby Output</b>	+15VDC
<b>Remote On/Off</b>	NO
<b>Protection</b>	OVP, OCP, SCP for All outputs
<b>Safety Agency Certification</b>	CSA
<b>Size (W x H x D)</b>	320 x 60.5 x 153(mm)

## ❖ Output Information

Output	Set Voltage	Tolerance @ Set Load	Set Load	Total Tolerance	Min Load	Max Load
1	32.0V	NA	NA	±3%	0A	1.25A
2	15.0V			±3%	1A	5A
3	15.0V			±5%	0A	0.7A
4	9.0V			±3%	0.2A	4A
5	5.2V			±2%	0.5A	7A
6	5.2V			-2% ~ +3%	0.5A	11A
7	3.4V			-2% ~ +3%	4A	15A
8	-5.2V			±2%	1A	9A
9	-15V			±3%	0.35A	3.5A